

Metrische schroefdraad



Voor het inbrengen in de uitsparingen met behulp van een tegenmoer (tegenmoer apart te bestellen)

KLEUR: Metaalkleur



Art. nr.	DRAAD (FT)	TYPE	IP-WAARDE	C° BEREIK DYN.	C° BEREIK STAT.
S10/M12/A	M12	A	IP40	-45 - +250	-350
SP12/M16/M	M16	M	IP65	-45 - +150	-200
SP10/M12/A	M12	A	IP54	-45 - +250	-350
S12/M16/A	M16	A	IP40	-45 - +250	-350
SPL16/M16/B	M16	B	IP67	-45 - +150	-215
SPL10/M12/M	M12	M	IP66, IP67, IP68 (10 bar 30 min), IP69K	-45 - +150	-215
SP10/M12/B	M12	B	IP54	-45 - +250	-350
SPB10/M12/B	M12	B	IP54	-45 - +250	-350
SB12/M16/B	M16	B	IP40	-45 - +250	-350
S10/M12/B	M12	B	IP40	-45 - +250	-350
SPL10/M12/A	M12	A	IP67	-45 - +150	-215
SP12/M16/B	M16	B	IP54	-45 - +250	-350
SB16/M16/B	M16	B	IP40	-45 - +250	-350
SPL10/M16/M	M16	M	IP66, IP67, IP68 (10 bar 30 min), IP69K	-45 - +150	-215
SPL16/M20/B	M20	B	IP67	-45 - +150	-215
SPL16/M16/A	M16	A	IP67	-45 - +150	-215
SP16/M16/M	M16	M	IP65	-45 - +150	-200
SPB12/M16/B	M16	B	IP54	-45 - +250	-350
S16/M16/A	M16	A	IP40	-45 - +250	-350
SP12/M16/A	M16	A	IP54	-45 - +250	-350
S12/M16/B	M16	B	IP40	-45 - +250	-350
S16/M20/A	M20	A	IP40	-45 - +250	-350
SB20/M20/B	M20	B	IP40	-45 - +250	-350
S16/M16/B	M16	B	IP40	-45 - +250	-350
SPB16/M16/B	M16	B	IP54	-45 - +250	-350

Art. nr.	DRAAD (FT)	TYPE	IP-WAARDE	C° BEREIK DYN.	C° BEREIK STAT.
SPL20/M20/B	M20	B	IP67	-45 - +150	-215
SP16/M16/B	M16	B	IP54	-45 - +250	-350
SP16/M20/M	M20	M	IP65	-45 - +150	-200
SP16/M16/A	M16	A	IP54	-45 - +250	-350
SPL12/M16/M	M16	M	IP66, IP67, IP68 (10 bar 30 min), IP69K	-45 - +150	-215
SPL16/M20/A	M20	A	IP67	-45 - +150	-215
SPL25/M25/A	M25	A	IP67	-45 - +150	-215
SP19/M20/M	M20	M	IP65	-45 - +150	-200
SB25/M25/B	M25	B	IP40	-45 - +250	-350
SPB20/M20/B	M20	B	IP54	-45 - +250	-350
SP16/M20/A	M20	A	IP54	-45 - +250	-350
S20/M20/A	M20	A	IP40	-45 - +250	-350
SP16/M20/B	M20	B	IP54	-45 - +250	-350
SPL16/M16/M	M16	M	IP66, IP67, IP68 (10 bar 30 min), IP69K	-45 - +150	-215
S16/M20/B	M20	B	IP40	-45 - +250	-350
SPL25/M25/B	M25	B	IP67	-45 - +150	-215
S25/M25/A	M25	A	IP40	-45 - +250	-350
SPL16/M20/M	M20	M	IP66, IP67, IP68 (10 bar 30 min), IP69K	-45 - +150	-215
SP20/M20/A	M20	A	IP54	-45 - +250	-350
SPL32/M32/B	M32	B	IP67	-45 - +150	-215
SP20/M20/B	M20	B	IP54	-45 - +250	-350
SP20/M20/M	M20	M	IP65	-45 +150	100
SB32/M32/B	M32	B	IP40	-45 - +250	-350
SPB25/M25/B	M25	B	IP54	-45 - +250	-350
S20/M20/B	M20	B	IP40	-45 - +250	-350
SP25/M25/B	M25	B	IP54	-45 - +250	-350
S32/M32/A	M32	A	IP40	-45 - +250	-350
SPL20/M20/M	M20	M	IP66, IP67, IP68 (10 bar 30 min), IP69K	-45 - +150	-215
S25/M25/B	M25	B	IP40	-45 - +250	-350
SP25/M25/M	M25	M	IP65	-45 - +150	-200
SB40/M40/B	M40	B	IP40	-45 - +250	-350
SPB32/M32/B	M32	B	IP54	-45 - +250	-350
SP25/M25/A	M25	A	IP54	-45 - +250	-350
SP32/M32/B	M32	B	IP54	-45 - +250	-350
SPL25/M25/M	M25	M	IP66, IP67, IP68 (10 bar 30 min), IP69K	-45 - +150	-215
SP32/M32/A	M32	A	IP54	-45 - +250	-350
S40/M40/A	M40	A	IP40	-45 - +250	-350
SPB40/M40/B	M40	B	IP54	-45 - +250	-350
SP32/M32/M	M32	M	IP65	-45 - +150	-200
S32/M32/B	M32	B	IP40	-45 - +250	-350
SPL32/M32/M	M32	M	IP66, IP67, IP68 (10 bar 30 min), IP69K	-45 - +150	-215
S40/M40/B	M40	B	IP40	-45 - +250	-350
SP40/M40/B	M40	B	IP54	-45 - +250	-350
SP40/M40/M	M40	M	IP65	-45 - +150	-200
S50/M50/A	M50	A	IP40	-45 - +250	-350
SP40/M40/A	M40	A	IP54	-45 - +250	-350
SP50/M50/B	M50	B	IP54	-45 - +250	-350

Art. nr.	DRAAD (FT)	TYPE	IP-WAARDE	C° BEREIK DYN.	C° BEREIK STAT.
S50/M50/B	M50	B	IP40	-45 - +250	-350
SP50/M50/A	M50	A	IP54	-45 - +250	-350
S63/M63/A	M63	A	IP40	-45 - +250	-350
SP50/M50/M	M50	M	IP65	-45 - +150	-200
SPL40/M40/M	M40	M	IP66, IP67, IP68 (10 bar 30 min), IP69K	-45 - +150	-215
SPL50/M50/M	M50	M	IP66, IP67, IP68 (10 bar 30 min), IP69K	-45 - +150	-215
S75/M75/A	M75	A	IP40	-45 - +250	-350
SP63/M63/A	M63	A	IP54	-45 - +250	-350
SP75/M75/A	M75	A	IP54	-45 - +250	-350
SPL63/M63/M	M63	M	IP66, IP67, IP68 (10 bar 30 min), IP69K	-45 - +150	-215